Revision Date 07-03-2014 Revision Number 10



SECTION 1 Identification of the substance/mixture and of the company/undertaking

Product identification used on label

Product identifier 3212

TECTYL 435D

Details of the supplier of the safety

data sheet

Daubert Chemical Company 4700 S. Central Avenue Chicago, IL 60638

708-496-7350

Emergency telephone number Relevant identified uses of the substance or mixture and uses

advised against

Chemtrec: (800) 424-9300 Corrosion Preventive Compound

SECTION 2 Hazards identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Classification Not classified as hazardous under

OSHA.

Hazard Statements Molten material can cause thermal

burns. When heated, the vapors/fumes given off may cause respiratory tract

irritation.

SECTION 3 Composition/information on ingredients

Chemical Name CAS # %

No Hazardous Components

Note: Specific chemical identities and/or exact percentages have been withheld as a trade secret.

SECTION 4 First aid measures

Inhalation This material does not present a hazard if inhaled. Remove individual to fresh air after an

airborne exposure if any symptoms develop, as a precautionary measure.

Eyes Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to

prevent chemical from transferring to the uncontaminated eye. Get immediate medical

attention.

Skin Contact Wash with soap and water. Remove contaminated clothing and launder. Get medical attention

if irritation develops or persists. If burned by contact with hot material, molten material adhering to skin should be cooled as quickly as possible with water and see a physician for

removal of adhering material and treatment of burn.

Ingestion Do not induce vomiting. Seek medical attention immediately. Provide medical care provider

with this SDS.

Note to Doctor Treat symptomatically.

TECTYL 435D Page 1 of 5

Revision Date 07-03-2014 Revision Number 10

Extinguishing media Use water fog, foam, dry chemical or carbon dioxide (CO2) to

extinguish flames.

Fire and/or Explosion Hazards Material may be ignited only if preheated to temperatures above the

high flash point, for example in a fire.

Fire Fighting Methods and Protection Do not enter fire area without proper protection including self-

contained breathing apparatus and full protective equipment. Use

appropriate methods for the surrounding fire. Oxides of carbon, Hydrocarbons, Sulfur oxides

Hazardous Combustion Products

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill

Methods and materials for containment and cleaning up

Collect and discard in accordance with local, state and national regulations.

SECTION 7 Handling and storage

Precautions for safe handling

Avoid contacting and avoid breathing the material. Use only in a well ventilated area. No special handling instructions due to toxicity. Avoid contact with molten material. When heated, the vapor/fumes given off may cause respiratory tract irritation.

Conditions for safe storage, including any incompatibilities

Incompatible materials

Store in a cool dry place. Isolate from incompatible materials.

Strong oxidizing agents, Strong acids

SECTION 8 Exposure controls/personal protection

Control	parameters

<u>Chemical Name</u> <u>ACGIH TLV</u> <u>ACGIH STEL</u> <u>OSHA PEL</u>

No data available No TLV

Engineering Measures Local exhaust ventilation or other engineering controls are normally required when

handling or using this product to avoid overexposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne

levels below recommended exposure limits

Respiratory Protection Respiratory protection may be required to avoid overexposure when handling this

product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions warrant the use of a

respirator.

TECTYL 435D Page 2 of 5

Revision Date 07-03-2014 Revision Number 10

Eye Protection Wear chemical splash goggles when handling this product. Additionally, wear a face

shield when the possibility of splashing of liquid exists. Do not wear contact lenses.

Have an eye wash station available.

Skin Protection Wear protective gloves. Inspect gloves for chemical break-through and replace at

regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. When handling material that has been heated, wear chemically resistant thermally insulating gloves, chemical resistant apron, long sleeves and other clothing as necessary to protect

against thermal burns.

Gloves Heat insulating chemically resistant gloves

SECTION 9 Physical and chemical properties (Typical, not specification)

Physical State Waxy Solid Color Amber

Odor Slight Petroleum Type **Odor Threshold** No data available No data available Melting Point, °C No data available Boiling Point, °C No data available **Flash Point** $> 430 \, {}^{\circ}\text{F}(221 \, {}^{\circ}\text{C})$ >1 (n-Butyl Acetate=1) **Evaporation Rate** Flammability (Solid, Gas) No data available Lower Flammable/Explosive Limit, No data available

% in air

Upper Flammable/Explosive Limit,

% in air

Vapor Pressure < 1 mmHg Vapor Density >1 (Air=1)

Specific Gravity 0.9

Solubility in Water
Octanol/Water Partition Coefficient
Autoignition Temperature
Decomposition Temperature
Viscosity
No data available

VOC, Method EPA 24, lb/gal 0.08 VOC, Method EPA 24, grams/liter 9

SECTION 10 Stability and reactivity

Chemical stability Stable under normal conditions. Hazardous polymerization

No data available

will not occur.

Possibility of hazardous reactions Strong oxidizing agents, Strong acids

Conditions to avoid Contamination.

Incompatible materials Strong oxidizing agents, Strong acids

Hazardous decomposition productsDecomposition and hazardous decomposition products are

unlikely.

TECTYL 435D Page 3 of 5

Revision Date 07-03-2014 Revision Number 10

SECTION 11 Toxicological information

Likely Routes of EntryInhalation, Ingestion, Skin contact, Eye contact

Target Organs Potentially Affected by Exposure No organs known to be damaged from exposure to this

product.

Chemical Interactions That Change Toxicity

Medical Conditions Aggravated

No chemical interaction known to affect toxicity. Skin contact may aggravate existing skin disease

Immediate (Acute) Health Effects by Route of Exposure

Inhalation Irritation Can cause minor respiratory irritation.

Inhalation Toxicity Non-Toxic. Not known to cause systemic damage.

Skin Contact Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause

permanent damage.

Skin Absorption No absorption hazard in normal industrial use.

Eye Contact Can cause moderate irritation, tearing and reddening, but not likely to permanently injure

eye tissue.

Ingestion Irritation Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea,

vomiting and diarrhea.

Ingestion Toxicity Harmful if swallowed.

Long-Term (Chronic) Health Effects

Carcinogenicity Not listed by ACGIH, IARC, NIOSH, NTP OR OSHA.

Reproductive and Developmental Toxicity No data available to indicate product or any components present at

greater than 0.1% may cause birth defects.

Mutagenicity No data available to indicate product or any components present at greater than 0.1% is

mutagenic or genotoxic.

Inhalation Upon prolonged and/or repeated exposure, can cause respiratory irritation. Can cause

systemic damage upon prolonged and/or repeated exposure (see "Target Organs)

Skin Contact Upon prolonged or repeated contact, can cause minor skin irritation, defatting, and

dermatitis.

Skin Absorption Upon prolonged or repeated exposure, no hazard in normal industrial use.

Component Toxicology Data

Chemical Name CAS Number LD50/LC50

No data available

SECTION 12 Ecological information

Overview No ecological information available

MobilityNo dataPersistenceNo dataBioaccumulationNo dataDegradabilityNo data

Ecotoxicity Data

Chemical Name CAS Number Aquatic EC50 Aquatic ERC50 Aquatic LC50

Crustacea Algae Fish

No data available

TECTYL 435D Page 4 of 5

Revision Date 07-03-2014 Revision Number 10

SECTION 13 Disposal considerations

Waste Description for Spent Product Spent or discarded material is non-hazardous according to

environmental regulations.

Disposal Methods Dispose of in accordance with Local and National regulations.

Waste Disposal Code(s) Not applicable

SECTION 14 Transport information

Full Shipping Name for Rust Inhibitor / Non-Hazardous

Export, Air, Sea (any

quantity) or vessels of 119 gal.

or more:

Domestic Ground in vessels < Not Hazardous

119 gal.

SECTION 15 Regulatory information

TSCA Status All components in this product are on the TSCA Inventory or exempt.

Chemical Name CAS # Regulation Percent

No 313-listed chemicals in this product SARA 313

SECTION 16 Other information

Revision 07-03-2014

Date

Disclaimer Although the information contained herein is believed to be reliable, it is furnished without warranty

of any kind. This information is not intended to be all-inclusive as to the manner and conditions of

use, handling, and storage.

Version Reviewed

Comments Approved: M. Longo

TECTYL 435D Page 5 of 5