Revision Date 11-24-2014 Revision Number 1



### SECTION 1 Identification of the substance/mixture and of the company/undertaking

Product identification used on label

Product identifier 3013

TECTYL 603

Details of the supplier of the safety

data sheet

Daubert Chemical Company 4700 S. Central Avenue

Chicago, IL 60638 708-496-7350

Emergency telephone number Relevant identified uses of the

substance or mixture and uses

advised against

Chemtrec: (800) 424-9300

Corrosion Preventative Compound

### **SECTION 2 Hazards identification**

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Classification Flammable Liquid Category 4

Signal Word Warning

Hazard Statements Combustible Liquid

**Precautionary Statements** 

Prevention Keep away from heat/sparks/open

flames/hot surfaces. – No smoking. Wear protective gloves/protective clothing/eye protection/face protection.

Response Use dry chemical, water fog, CO2, foam

or sand/earth for extinction.

Storage Store in a well-ventilated place. Keep

cool.

Disposal Dispose of contents/container in

accordance with

local/regional/national/international regulation for hazardous wastes.

### **SECTION 3 Composition/information on ingredients**

Chemical Name	CAS#	%
Stoddard solvent	8052-41-3	3 - 7
Ethylene glycol mono-n-butyl ether	111-76-2	1 - 5

Note: Specific chemical identities and/or exact percentages have been withheld as a trade secret.

TECTYL 603 Page 1 of 6

Revision Date 11-24-2014 Revision Number 1

### **SECTION 4 First aid measures**

**Inhalation** If symptoms are experienced remove source of contamination or move victim to fresh air and

obtain medical advice.

**Eves** Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often.

Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate

medical attention and monitor the eye daily as advised by your physician.

**Skin Contact** Wash with soap and water. Remove contaminated clothing and launder. Get medical attention

if irritation develops or persists.

**Ingestion** Do not induce vomiting and seek medical attention immediately. Provide medical care

provider with this SDS. Do not induce vomiting. Get immediate medical attention. Careful

evacuation of stomach by medical personnel imperative.

**Note to Doctor** Treat symptomatically.

# **SECTION 5 Firefighting measures**

**Extinguishing media**Use alcohol resistant foam, carbon dioxide, or dry chemical

extinguishing agents. Water may be ineffective but water spray can be used extinguish a fire if swept across the base of the flames. Water can absorb heat and keep exposed material from being damaged by fire.

Fire and/or Explosion Hazards

Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause

an explosion that may lead to injury or death.

Fire Fighting Methods and Protection Do not enter fire area without proper protection including self-contained

breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or

equivalent) and full protective gear.

Flammable component(s) of this material may be lighter than water and

burn while floating on the surface.

Use appropriate methods for the surrounding fire.

Hazardous Combustion Products Oxides of carbon, Toxic fumes, Toxic gases, Hydrocarbons, Sulfur

compounds

#### **SECTION 6 Accidental release measures**

Personal precautions, protective equipment and emergency procedures

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

TECTYL 603 Page 2 of 6

Revision Date 11-24-2014 Revision Number 1

# Methods and materials for containment and cleaning up

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

materials Store in a cool place in original container and protect

from sunlight. Limit quantity of material stored.

# **SECTION 7 Handling and storage**

Precautions for safe handling	Avoid contacting and avoid breathing the material. Use only in a	
	well ventilated area. As with all chemicals, good industrial	
	hygiene practices should be followed when handling this	
	material. Wash thoroughly after handling. Do not get in eyes, on	
	skin and clothing. "Empty" containers retain product residue	
	(liquid and/or vapor) and can be dangerous. Use spark-proof tools	
	and explosion-proof equipment. Do not use pressure to empty	
	container. Follow all SDS/label precautions even after container	
	is emptied because it may retain product residues	
Conditions for safe storage, including any	Store in a cool dry place. Isolate from incompatible	
incompatibilities	materials. Keep away from sources of ignition. Store in tightly	
_	sealed original container. Do not store near combustible	

**Incompatible materials** 

Strong oxidizing agents, Strong alkalies

### **SECTION 8 Exposure controls/personal protection**

Control parameters Chemical Name	ACGIH TLV	ACGIH STEL	OSHA PEL
Stoddard solvent	100 ppm TWA; 525 mg/m3 TWA		500 ppm TWA; 2900 mg/m3 TWA
Ethylene glycol mono-n-butyl ether	20 ppm TWA; 96 mg/m3 TWA		50 ppm TWA; 240 mg/m3 TWA

#### **Engineering Measures**

Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits Explosion proof exhaust ventilation should be used

# **Respiratory Protection**

Proper ventilation (at a minimum) will be required when handling this product. Use respirators (NIOSH approved) only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions warrant the use of a respirator. Respiratory protection may be required in addition to ventilation depending upon conditions of use. Wear a NIOSH approved respirator if any exposure is possible.

TECTYL 603 Page 3 of 6

Revision Date 11-24-2014 Revision Number 1

**Eye Protection** Wear chemically resistant safety glasses with side shields when handling this product.

Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne

material. Do not wear contact lenses. Have an eye wash station available.

**Skin Protection** Wear protective gloves. Inspect gloves for chemical break-through and replace at

No data available

regular intervals. Clean protective equipment regularly. Wash hands and other exposed

areas with mild soap and water before eating, drinking, and when leaving work.

Gloves Chemically resistant gloves

# **SECTION 9 Physical and chemical properties (Typical, not specification)**

Physical State Liquid Color Amber

Odor Slight Ester-like Sweet **Odor Threshold** No data available pН 8.1 @ 20% Melting Point, °C No data available Boiling Point, °C No data available **Flash Point** 148 °F( 64 °C) **Evaporation Rate** No data available Flammability (Solid, Gas) No data available

Lower Flammable/Explosive Limit,

% in air

Upper Flammable/Explosive Limit, No data available

% in air

Vapor Pressure 0.66 mmHg

Specific Gravity @ 25°C 0.92

Solubility in WaterComplete; 100%Octanol/Water Partition CoefficientNo data availableAutoignition TemperatureNo data availableDecomposition TemperatureNo data availableViscosity83 cSt @ 40°C

Volatiles, % by weight 6 VOC, Method EPA 24, lb/gal 0.46 VOC, Method EPA 24, grams/liter 55.2

#### **SECTION 10 Stability and reactivity**

Chemical stability Stable under normal conditions. Hazardous polymerization

will not occur.

**Possibility of hazardous reactions**Under normal conditions of storage and use, hazardous

reactions will not occur.

**Conditions to avoid** Contamination.

Incompatible materials Strong oxidizing agents, Strong alkalies

Hazardous decomposition products Decomposition and hazardous decomposition products are

unlikely.

TECTYL 603 Page 4 of 6

Revision Date 11-24-2014 Revision Number 1

# **SECTION 11 Toxicological information**

Likely Routes of Entry

Target Organs Potentially Affected by Exposure
Chemical Interactions That Change Toxicity

Skin contact, Inhalation, Eye contact, Absorption
Eyes, Skin, Nervous System, Respiratory Tract, Lungs
No chemical interaction known to affect toxicity.

Medical Conditions Aggravated

Skin contact may aggravate existing skin disease, Respiratory disease including asthma and bronchitis, Lung disease

Immediate (Acute) Health Effects by Route of Exposure

**Inhalation Irritation** Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and

headache.

**Inhalation Toxicity** Can cause systemic damage (see "Target Organs)

**Skin Contact** Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause

permanent damage.

**Skin Absorption** May cause irritation and minor systemic damage.

**Eye Contact** Contact with the eyes may cause moderate to severe eye injury. Eye contact may result

in tearing and reddening, but not likely to permanently injure eye tissue. Temporary

vision impairment (cloudy or blurred vision) is possible.

**Ingestion Irritation** Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea,

vomiting and diarrhea. Aspiration of material into the lungs can cause chemical

pneumonitis which can be fatal.

**Ingestion Toxicity** Harmful if swallowed.

**Long-Term (Chronic) Health Effects** 

Carcinogenicity This product contains mineral oils which are considered to be severely refined and not

considered to be carcinogenic under IARC. All of the oils in this product have been

demonstrated to contain less than 3% extractables by the IP 346 test.

Reproductive and Developmental Toxicity No data available to indicate product or any components present at

greater than 0.1% may cause birth defects. Possible reproductive

hazard.

**Mutagenicity** No data available to indicate product or any components present at greater than 0.1% is

mutagenic or genotoxic.

**Inhalation** Upon prolonged and/or repeated exposure, can cause severe respiratory irritation,

dizziness, weakness, fatigue, nausea, headache and possible unconsciousness. Can cause

systemic damage upon prolonged and/or repeated exposure (see "Target Organs)

Skin Contact Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and

dermatitis. Not likely to cause permanent damage.

**Skin Absorption** Upon prolonged or repeated exposure, harmful if absorbed through the skin. May cause

severe irritation and systemic damage.

**Component Toxicology Data** 

Chemical Name
Stoddard solvent

8052-41-3

Dermal LD50 Rabbit > 3000 mg/kg
Dermal LD50 Rat > 2000 ml/kg Oral LD50 Rat > 5000 mg/kg
Inhalation LC50 (4h) Rat > 5500 MG/CU M
Dermal LD50 Rat > 2000 ml/kg Oral LD50 Rat = 1300
mg/kg
Dermal LD50 Guinea pig > 2000 ml/kg Oral LD50 Rat = 1300
mg/kg
Oral LD50 Guinea pig = 1400 mg/kg Inhalation LC50 (4h) Rat > 5
mg/L
Inhalation LC50 (1h) Guinea pig > 3 mg/L

TECTYL 603 Page 5 of 6

Revision Date 11-24-2014 **Revision Number 1** 

#### **SECTION 12 Ecological information**

Overview No ecological information available

**Mobility** No data **Persistence** No data No data Bioaccumulation **Degradability** No data

**Ecotoxicity Data** 

**Chemical Name CAS Number Aquatic EC50 Aquatic ERC50 Aquatic LC50** Crustacea Fish Algae

EC50 (48 hr) Ethylene glycol mono-n-butyl 111-76-2 EC50 (72 hr) Algae LC50 (96 hr) Water flea > 1550 ether = 1840 mg/LRainbow trout =

mg/L 1474 mg/L

**SECTION 13 Disposal considerations** 

**Waste Description for Spent Product** Spent or discarded material is a hazardous waste.

**Disposal Methods** Dispose of by incineration following Federal, State, Local, or Provincial

regulations.

Waste Disposal Code(s) D001

**SECTION 14 Transport information** 

UN1268, PETROLEUM DISTILLATES, N.O.S., (Naphtha Solvent), 3, PG III **Full Shipping Name for** 

Export, Air, Sea (any

quantity) or vessels of 119 gal.

or more:

**Domestic Ground in vessels <** Not Regulated

119 gal.

**SECTION 15 Regulatory information** 

All components in this product are on the TSCA Inventory or exempt. **TSCA Status** 

Not all components of this product have been verified to be on the Canadian DSL or NDSL. **Canadian DSL** 

status:

**Chemical Name** CAS# Regulation Percent **SARA 313** Glycol ethers (N230) 111-76-2 1 - 51 - 5 93820-55-4 **SARA 313 Barium compounds** 

# **SECTION 16 Other information**

Revision 11-24-2014

**Date** 

Disclaimer Although the information contained herein is believed to be reliable, it is furnished without warranty

of any kind. This information is not intended to be all-inclusive as to the manner and conditions of

use, handling, and storage.

Version Original

**Comments** Approved: J. Kump / M. Duncan

Page 6 of 6 TECTYL 603