



Quaker State® Dexron®-VI

Automatic Transmission Lubricant

QUAKER STATE® Dexron®-VI Automatic Transmission Fluid is an exceptional automatic transmission fluid approved by General Motors for use in vehicles with automatic transmissions. It is specially formulated to provide twice the service life of a Dexron®-III(H) ATF and offers enhanced performance for both new and older transmissions. It is designed to protect transmissions through improved oxidation resistance, friction durability, shear stability and wear protection to help meet warranty protection requirements in late model vehicles.

Applications

QUAKER STATE® Dexron®-VI Automatic Transmission Fluid is recommended for all 2006 and beyond GM vehicles with Hydra-Matic automatic transmissions. It is fully back serviceable for Dexron®-III (H), III and IIE applications. Meets GM specification GMN10060. Always consult your vehicle owner's manual for specific recommendation.

Performance Features and Benefits

- Extended fluid life vs. Dexron®-III (H) ATF and helps extend the life of the transmission
- Outstanding resistance against sludge and deposit formation
- Improved oxidation and thermal stability vs. Dexron®-III (H) ATF
- Superior anti-wear protection vs. Dexron®-III (H) ATF
- Outstanding low temperature fluidity
- Enhanced foam control which maintains responsive shifts and reduces wear on bearings, bushing and gears

- Helps prevent clutch shudder in modulated torque converters
- Improved torque transfer vs. Dexron®-III (H) ATF
- Improved shear stability vs. Dexron®-III (H) ATF

Specifications and Approvals

- QUAKER STATE® Dexron®-VI Automatic Transmission Fluid is recommended for all 2006 and beyond GM vehicles with Hydra-Matic automatic transmissions.
- QUAKER STATE® Dexron®-VI Automatic Transmission Fluid meets GM specification GMN10060

Health & Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet, which can be obtained from your Shell representative.

Protect the environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Typical Physical Characteristics

Property	Test Method	Typical Results
Density, kg/l @ 15°C	ASTM D4052	0.846
Kinematic Viscosity		
cSt @ 40°C	ASTM D-445	29.8
cSt @ 100°C	ASTM D-445	6.0
Viscosity Index	ASTM D2270	151
Total Base No.	ASTM D2896	2.0
Flash Point °C / °F	ASTM D92	206 / 403
Brookfield Viscosity		
cSt @ -20°C	ASTM D2983	1,053
cSt @ -30°C		3,164
cSt @ -40°C		12,030
Pour Point °C / °F	ASTM D97	-54 / -65
Sulphated Ash, % wt	ASTM D874	0.02
Color	-	Red

These characteristics are typical of current production. While future production will conform to SOPUS Products specifications, variations in these characteristics may occur.

Dexron® is a registered trademark of General Motors Corporation.